Contents

1. Introduction

2. Fundamental properties of microtremors

- 2.1.What are Microtremors?
- 2.2.Power spectra of microtremors
- 2.3. Temporal and spatial variation of microtremors
 - 2.3.1. Temporal variation of microtremors
 - 2.3.2. Spatial variation of microtremors

3. Principle of the microtremor survey method

- 3.1. The microtremor survey method (MSM)
 - 3.1.1. Wave type used in microtremor surveys
 - 3.1.2. From dispersion of surface waves to subsurface structure
- 3.2. Spectral representation of microtremors
 - 3.2.1. Spectral representation of a stochastic process
 - 3.2.2. Spectral representation of microtremors
- 3.3.Detection of surface waves
- 3.4.Detection of Rayleigh waves from vertical component of microtremors (frequencywavenumber method)
 - 3.4.1. Frequency-wavenumber power spectral density function
 - 3.4.2. Beam-forming method
 - 3.4.3. Maximum likelihood method or high-resolution method - - OMITTED
 - 3.4.4. Phase velocity and direction of wave propagation
 - 3.4.5. Calculation of cross-spectra by block averaging ----- OMITTED
- 3.5.Detection of Rayleigh waves from the vertical component of microtremors (spatial autocorrelation method)
 - 3.5.1. Spectral representation of microtremors in a polar coordinate system
 - 3.5.2. The spatial autocorrelation function and the spatial covariance function
 - **3.5.3**. The spatial autocorrelation coefficient of a circular array and its relation to phase velocity
- 3.6.Detection of Love waves from microtremors (spatial autocorrelation method)
 - 3.6.1. The spectral representation of horizontally polarized waves in microtremors
 - 3.6.2. The spatial autocorrelation function for horizontally polarized waves
 - **3.6.3**. The spatial autocorrelation coefficient for horizontally polarized waves and wavenumber equation of Love waves

4. Estimating phase velocity and subsurface structure

- 4.1.Estimating phase velocity
 - 4.1.1. Spatial autocorrelation (SPAC) method
 - 4.1.2. Spatial autocorrelation method with different arrays (ESPAC method)
- 4.2. Estimating subsurface structure from phase velocity
 - 4.2.1. Procedure for estimating subsurface structure
 - 4.2.2. Inversion
 - 4.2.3. Estimating adjustment parameters

- 4.2.4. Calculation procedure
- 4.2.5. Effective variables for refining a model

5. Data acquisition and analysis methods

- 5.1.Observing microtremors
 - 5.1.1. Observation array
 - 5.1.2. Data acquisition system
 - 5.1.3. Time for data collection
- 5.2.Data analysis
 - 5.2.1. Data analysis by frequency-wavenumber method
 - 5.2.2. Data analysis by spatial autocorrelation method
 - 5.2.3. Case history of estimating phase velocity

6. Case histories

6.1. Application of the frequency-wavenumber (f-k) method

- 6.1.1. Regional structural survey by long-period microtremors
- 6.1.2. Comparison of the result with a reflection seismic survey
- 6.2. Application of the spatial autocorrelation method
 - 6.2.1. Evaluating reliability of the spatial autocorrelation method by comparing with wireline log data
 - 6.2.2. Estimating three-dimensional shallow and deep subsurface structures in the central Kanto Plain, Japan

7. Closing Remarks